

Quote Form: PVCu Sliding Sash Windows

**Units 1-3 Red Barns
Warners Farm
Howe Street
Great Waltham
Chelmsford
Essex
CM3 1BN
Tel: 01245 362236**

Customer Details	
Name	<input type="text"/>
Address	<input type="text"/>
	<input type="text"/>
	<input type="text"/>
Tel	<input type="text"/>
Fax	<input type="text"/>
Mobile	<input type="text"/>
Email	<input type="text"/>

Project Details	
Collect <input type="checkbox"/>	Deliver <input type="checkbox"/>
Required Date (week commencing)	<input type="text"/>
Delivery Address	<input type="text"/>
	<input type="text"/>
	<input type="text"/>
Delivery Contact	<input type="text"/>
Delivery Telephone	<input type="text"/>
Customer Reference	<input type="text"/>
Customer Order No	<input type="text"/>



Project Type: New build Refurbishment Subject to Building Regs





Specification Section - Window 1

Quantity	<input type="text"/>
Location	<input type="text"/>
Width (mm) Min 350mm	<input type="text"/>
Height (mm) Min 800mm	<input type="text"/>
Transom Drop (from top)	<input type="text"/>
Viewed from outside	<input type="text"/>

Special instructions:

Frame Options
Window Colour External <input type="checkbox"/> White smooth <input type="checkbox"/> White woodgrain <input type="checkbox"/> Cream woodgrain <input type="checkbox"/> Golden oak <input type="checkbox"/> Irish oak <input type="checkbox"/> Rosewood <input type="checkbox"/> Black woodgrain <input type="checkbox"/> Chartwell green <input type="checkbox"/> Grey (RAL 7016) <input type="checkbox"/> Living oak <input type="checkbox"/> Bespoke colour (Enter RAL in instructions below)
Window Colour Internal <input type="checkbox"/> Smooth white <input type="checkbox"/> To match external NB: colour on white windows have no top sash till facility.
Sills inc in overall height <input type="checkbox"/> 150mm with up-stand (0mm projection) <input type="checkbox"/> 150mm without up-stand (15mm projection) <input type="checkbox"/> 180mm without up-stand (45mm projection) <input type="checkbox"/> 225mm without up-stand (90mm projection)
Add-ons (external only) specify other if required (inc in overall width & height) <input type="checkbox"/> 30mm <input type="checkbox"/> 50mm <input type="checkbox"/> Top <input type="checkbox"/> Left <input type="checkbox"/> Right

Hardware
Hardware colours <input type="checkbox"/> White <input type="checkbox"/> Gold <input type="checkbox"/> Chrome <input type="checkbox"/> Satin silver <input type="checkbox"/> Black <input type="checkbox"/> Graphite <input type="checkbox"/> Bronze <input type="checkbox"/> Antique black
Hardware style <input type="checkbox"/> Standard - locking <input type="checkbox"/> Standard - non-locking <input type="checkbox"/> Heritage - locking <input type="checkbox"/> Heritage - non-locking
 standard  heritage
Safety Restrictors <input type="checkbox"/> White <input type="checkbox"/> Gold <input type="checkbox"/> Chrome <input type="checkbox"/> Satin silver <input type="checkbox"/> Security Upgrade (hardware only) <input type="checkbox"/> Secured by Design (includes laminated glass) <input checked="" type="checkbox"/> Lift Hooks x2 per window <input type="checkbox"/> D-Handles x2 per window <input type="checkbox"/> Pole Eyes x2 per window

Extras
<input type="checkbox"/> Trickle Vent (top sash only) <input type="checkbox"/> Fire escape <input type="checkbox"/> Quick release tilt arms <input type="checkbox"/> Fixing brackets (9 per window) <input type="checkbox"/> Plant on Sash Horns <input type="checkbox"/> Run-through Sash Horns (mechanical) Deep Bottom Rail (150mm up-stand sill only) <input type="checkbox"/> Mechanical <input type="checkbox"/> Welded <input type="checkbox"/> Bay poles & couplers <input type="checkbox"/> Welded sill <input type="checkbox"/> Load-bearing jacking kits <input type="checkbox"/> Seamless Welding (woodgrain only; min width 475mm)
   

Glazing
Energy Rating (U Value) <input type="checkbox"/> 1.4W/m2K A+ <input type="checkbox"/> 1.5W/m2K A <input type="checkbox"/> 1.4W/m2K B Acoustic; laminated
Obscure Glass <input type="checkbox"/> Satin <input type="checkbox"/> Standard obscure Pattern <input type="text"/> <input type="checkbox"/> Top <input type="checkbox"/> Bottom
Spacer Bar Colour <input type="checkbox"/> Grey <input type="checkbox"/> White <input type="checkbox"/> Black
Toughened Glass <input type="checkbox"/> Top <input type="checkbox"/> Bottom
Glazing bars illustrate layouts <input type="checkbox"/> Astragal Bar (surface) <input type="checkbox"/> Internal Fret
Bar Layout <input type="checkbox"/> Single vertical bar <input type="checkbox"/> Grid <input type="checkbox"/> No. of squares across <input type="checkbox"/> No. of squares down

Specification Section - Window 2

Specification as previous

Quantity

Location

Width (mm)
 Min 350mm

Height (mm)
 Min 800mm

Transom Drop (From top)

Viewed from outside



Special instructions:

Frame Options

Window Colour External

- White smooth
- White woodgrain
- Cream woodgrain
- Golden oak
- Irish oak
- Rosewood
- Black woodgrain
- Chartwell green
- Grey (RAL 7016)
- Living oak
- Bespoke colour
(Enter RAL in instructions below)

Window Colour Internal

- Smooth white
- To match external

NB: colour on white windows have no top sash tilt facility.

Sills

inc in overall height

- 150mm with up-stand (0mm projection)
- 150mm without up-stand (15mm projection)
- 180mm without up-stand (45mm projection)
- 225mm without up-stand (90mm projection)

Add-ons

(external only)
 specify other if required
 (inc in overall width & height)

- 30mm
- 50mm
- Top
- Left Right

Hardware

Hardware colours

- White
- Gold
- Chrome
- Satin silver
- Black
- Graphite
- Bronze
- Antique black

Hardware style

- Standard - locking
- Standard - non-locking
- Heritage - locking
- Heritage - non-locking



Safety Restrictors

- White
- Gold
- Chrome
- Satin silver
- Security Upgrade (hardware only)
- Secured by Design (includes laminated glass)
- Lift Hooks x2 per window
- D-Handles x2 per window
- Pole Eyes x2 per window

Extras

- Trickle Vent (top sash only)
- Fire escape
- Quick release tilt arms
- Fixing brackets (9 per window)
- Plant on Sash Horns



- Run-through Sash Horns (mechanical)



Deep Bottom Rail (150mm up-stand sill only)

- Mechanical
- Welded



- Bay poles & couplers
- Welded sill
- Load-bearing jacking kits

- Seamless Welding (woodgrain only; min width 475mm)



Glazing

Energy Rating (U Value)

- 1.4W/m2k A+
- 1.5W/m2k A
- 1.4W/m2k B Acoustic; laminated

Obscure Glass

- Satin
 - Standard obscure
- Pattern
- Top
 - Bottom

Spacer Bar Colour

- Grey
- White
- Black

Toughened Glass

- Top
- Bottom

Glazing bars

illustrate layouts

- Astragal Bar (surface)
- Internal Fret

Bar Layout

- Single vertical bar
- Grid
- No. of squares across
- No. of squares down

Specification Section - Window 3

Specification as previous

Quantity

Location

Width (mm)
 Min 350mm

Height (mm)
 Min 800mm

Transom Drop (From top)

Viewed from outside



Special instructions:

Frame Options

Window Colour External

- White smooth
- White woodgrain
- Cream woodgrain
- Golden oak
- Irish oak
- Rosewood
- Black woodgrain
- Chartwell green
- Grey (RAL 7016)
- Living oak
- Bespoke colour
(Enter RAL in instructions below)

Window Colour Internal

- Smooth white
- To match external

NB: colour on white windows have no top sash tilt facility.

Sills

inc in overall height

- 150mm with up-stand (0mm projection)
- 150mm without up-stand (15mm projection)
- 180mm without up-stand (45mm projection)
- 225mm without up-stand (90mm projection)

Add-ons

(external only)
 specify other if required
 (inc in overall width & height)

- 30mm
- 50mm
- Top
- Left Right


Hardware

Hardware colours

- White
- Gold
- Chrome
- Satin silver
- Black
- Graphite
- Bronze
- Antique black

Hardware style

- Standard - locking
- Standard - non-locking
- Heritage - locking
- Heritage - non-locking



Safety Restrictors

- White
- Gold
- Chrome
- Satin silver
- Security Upgrade (hardware only)
- Secured by Design (includes laminated glass)
- Lift Hooks x2 per window
- D-Handles x2 per window
- Pole Eyes x2 per window

Extras

- Trickle Vent (top sash only)
- Fire escape
- Quick release tilt arms
- Fixing brackets (9 per window)
- Plant on Sash Horns



- Run-through Sash Horns (mechanical)



Deep Bottom Rail (150mm up-stand sill only)

- Mechanical
- Welded



- Bay poles & couplers
- Welded sill
- Load-bearing jacking kits

- Seamless Welding (woodgrain only; min width 475mm)



Glazing

Energy Rating (U Value)

- 1.4W/m2k A+
- 1.5W/m2k A
- 1.4W/m2k B Acoustic; laminated

Obscure Glass

- Satin
 - Standard obscure
- Pattern
- Top
 - Bottom

Spacer Bar Colour

- Grey
- White
- Black

Toughened Glass

- Top
- Bottom

Glazing bars

illustrate layouts

- Astragal Bar (surface)
- Internal Fret

Bar Layout

- Single vertical bar
- Grid
- No. of squares across
- No. of squares down